





CYCLE FLEX MINIATURE CABLE SPECIFICATIONS




1 x 7

Cycle Flex Part No. Bare	Nominal Bare Dia. in./mm	Cycle-Flex Part No. Coated w/ PC-100	Nominal Coated Dia. in./mm	Min. Breaking Strength Lb./Kg.	Min. Recommended Pulley Dia. in./mm	"C" Rating	"F" Rating	"EA" Value x10 ³	Weight per M Ft. Lb./Kg.
CF-0612S	.006/ .15	CF-0614S	.010/ .25	5/ 2.3	.80/ 20.32	.022	43	.47	.10/ .045
CF-0912S	.009/ .23	CF-0914S	.013/ .33	13/ 5.9	1.20/ 30.48	.049	65	1.06	.22/ .10
CF-1212S	.012/ .30	CF-1214S	.016/ .41	25/ 11.3	1.60/ 40.64	.088	86	1.89	.48/ .22
CF-1812S	.018/ .46	CF-1814S	.024/ .61	40/ 18.1	2.40/ 60.96	.198	129	4.26	1.07/ .49
CF-2412S	.024/ .61	CF-2414S	.030/ .76	85/ 38.6	3.20/ 81.28	.352	172	7.56	1.78/ .81
CF-2712S	.027/ .69	CF-2714S	.034/ .86	125/ 56.7	3.60/ 91.44	.445	194	9.57	2.28/ 1.03
CF3112S	.031/ .79	CF-3114S	.039/ .99	125/ 56.7	4.13/ 104.90	.566	218	12.17	2.96/ 1.34




1 x 19

CF-1032S*	.010/ .25	CF-1034S*	.014/ .36	19/ 8.6	.80/ 20.32	.060	42	1.25	.38/ .172
CF-1532S*	.015/ .38	CF-1534S*	.021/ .53	30/ 13.6	1.20/ 30.48	.134	63	2.82	.79/ .36
CF-2632S*	.026/ .66	CF-2634S*	.033/ .84	80/ 36.4	2.08/ 52.83	.382	106	8.02	1.74/ .79




7 x 7

CF-0952S	.009/ .23	CF-0954S	.013/ .33	7.5/ 3.4	.41/ 10.41	.038	19	.73	.26/ .12
CF-1452S	.014/ .36	CF-1454S	.018/ .46	20/ 9.07	.64/ 16.26	.099	30	1.88	.51/ .23
CF-1852S	.018/ .46	CF-1854S	.024/ .61	40/ 18.1	.80/ 20.32	.154	38	2.93	.86/ .39
CF-2352S*	.023/ .58	CF-2354S*	.030/ .76	60/ 27.3	1.00/ 25.40	.241	48	4.58	1.35/ .613
CF-2752S*	.027/ .69	CF-2754S*	.034/ .86	90/ 40.8	1.20/ 30.48	.346	57	6.58	1.64/ .75
CF-3252S	.032/ .81	CF-3254S	.040/ 1.02	115/ 52.1	1.40/ 35.56	.418	62	7.94	2.00/ .91
CF-3752S	.037/ .94	CF-3754S	.047/ 1.19	160/ 72.6	1.60/ 40.64	.616	76	11.70	2.99/ 1.36



7 x 19

CF-1572S	.015/ .38	CF-1574S	.021/ .53	35/ 15.9	.40/ 10.16	.104	17	1.78	.71/ .32
CF-1872S	.018/ .46	CF-1874S	.024/ .61	40/ 18.1	.48/ 12.19	.150	20	2.56	.93/ .42
CF-2472S*	.024/ .61	CF-2474S*	.030/ .76	70/ 31.8	.64/ 16.26	.267	27	4.55	1.45/ .65
CF-3072S*	.030/ .76	CF-3074S*	.037/ .94	120/ 54.4	.80/ 20.32	.418	34	7.10	1.98/ .90
CF-3872S*	.038/ .97	CF-3874S*	.048/ 1.22	175/ 79.5	1.00/ 25.40	.653	43	11.10	2.71/ 1.23
CF-4572S*	.045/ 1.14	CF-4574S*	.062/ 1.57	225/ 102.2	1.20/ 30.48	.940	51	15.98	4.6/ 2.09



7 x 7 x 7

CF-2782S	.027/ .69	CF-2784S	.034/ .86	80/ 36.4	.40/ 10.16	.269	16	4.31	1.70/ .77
CF-4482S*	.044/ 1.12	CF-4484S*	.053/ 1.35	150/ 68.0	.65/ 16.51	.690	26	11.04	2.67/ 1.21

Note: Cycle-Flex Cable normally available in stock as pre-stretched.

- NOTE:** 1. Standard tolerances for all bare and coated diameters upto and including CF-3874S is ± 0.002 " (± 0.05 mm). CF-4482S thru CF-4574S is ± 0.004 " (± 0.10 mm).
2. Most Cycle-Flex cable can be ordered as pre-stretched. To specify pre-stretched cables add the suffix "PS" to the Cycle-flex part number.